



The MULDIPOL™ Multiple Dipole Collinear Array concept has been specifically developed by TACO for ground-air-ground, air traffic control and associated vehicular and base communications applications. This omni directional concept employs a unique method of shielding the feed cables to improve radiation pattern characteristics. The MULDIPOL™ also has a high degree of isolation between discrete elements within a closely spaced array. The result is a small, rugged, easy to install antenna. The lightweight and compact design minimizes space and lends itself to tactical transportable use in the most hostile environments. A minimum of 30 dB isolation is realized between any two antenna elements in every MULDIPOL™ model. The low profile of this antenna plus the resulting decrease in the number of antennas required at any tower site also gives a much improved radiation pattern coverage.

Features

- Rugged lightweight construction • Transportable
- Compact • Combination of UHF and VHF
- High isolation between antenna elements
- Fibreglass Base (Metallic Base optional - see D5000 series)
- No DC ground (DC Grounded Dipoles optional - see D5000 series)

Specifications

Environmental

- Built to Military standards
- Rain, salt-fog, sand, dust and fungus to MIL-STD. 810A & B
- Temperature, barometric pressure and humidity to MIL-STD. 210 & 210A

Electrical

- Isolation (min.) 30.0 dB
- Polarization Vertical
- Omni Directional: ± 1.0 Uniformity (azimuth)
- VSWR (max.) 2:1
- Terminals "N" Female
- Terminal Impedance 50 Ohms
- Applied Power 100 W
- Vertical Beam Deviation $\pm 10^\circ$

Operation

The process employed in the TACO antennas incorporates the patented M U L D I P O L™ concept. The utilization of this technique results in a unit which has excellent "broadband" halfwave dipole characteristics over the entire operating frequencies. The desired "figure eight" radiation pattern is generally constant throughout the band. Through "broadband" suppression of extraneous currents upon the transmission line, the undesirable "Clover Leaf" pattern is avoided.

TACO Air Traffic Control FAA Antennas World Wide Use

MODEL	VHF (MHz)	UHF (MHz)	GAIN (dBic)	# OF OUTPUTS	HPBW DEGREE	MOUNTING DIAMETER	LENGTH INCHES	LENGTH CM	WEIGHT LBS	WEIGHT KG	COLOR	WIND LOAD WITH .5 ICE AREA (sq.ft.)
	118-136	225-400										
D4061A1	XX		4.0	1	40	2.5" IPS	136.63	318.75	19.0	8.64	White	2.1
D4062A		XX	4.0	1	40	2.5" IPS ^①	69.38	165.0	13.5	6.14	White	1.1
D4071	X	XX	1.0	3	75	2.5" IPS	115.50	293.37	16.8	7.63	White	1.8
D4072	XX		1.0	2	75	2.5" IPS	153.13	381.0	18.0	8.39	White	2.3
D4073	X	X	1.0	2	75	2.5" IPS	85.13	213.50	12.0	5.46	White	1.3
D4074		XX	1.0	2	75	2.5" IPS	85.13	216.0	12.0	5.46	White	1.3
D4076	X		1.0	1	75	2.5" IPS ^①	55.50	130.0	6.0	2.73	White	0.7
D4077		X	1.0	1	75	2.5" IPS ^①	33.19	84.30	4.9	2.16	White	0.4
D4078		XXX	1.0	3	75	2.5" IPS	115.50	293.37	16.8	7.63	White	1.8

X – Denotes number of active elements ① 1.25 inch (3.175 cm) IPS Pipe Mount with Optional Adapter. (2.5 inch IPS = 6.35 cm IPS)

TACO Communications Inc.

5512 Bearcreek Drive,
Mechanicsburg, PA. 17050
Tel: 717.975.0885 Fax: 717.763.0469
Email: tacocomm@aol.com
Web Site: www.tacocommunications.com

TACO Communications Inc.

29 Sharp Road
Brantford, Ontario,
N3T 5L8
Canada